

RANGER CREW XP 1000 Premium

Azure Crystal Metallic



Key Specifications

82
HP

6
PERSON CAPACITY

13"
GROUND CLEARANCE

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke Twin Cylinder DOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	82 HP
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

DIMENSIONS

Bed Box Dimensions (L x W x H)	36.75 x 54.25 x 12.5 in (93.3 x 137.8 x 31.75 cm)
Box Capacity	1,000 lbs (453.6 kg)
Estimated Dry Weight	1,894 lbs. (859 kg)
Fuel Capacity	11.5 gal (43.5 L)
Ground Clearance	13 in (33 cm)
GVW	3,750 lb (1,700.9 kg)
Hitch Towing Rating	2,500 lb (1,134 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Overall Vehicle Size (L x W x H)	152 x 62.5 x 77 in.(386 x 158 x 196 cm)
Payload Capacity	1,690 lbs. (767 kg)
Person Capacity	6

Wheelbase	113 in (287 cm)
-----------	-----------------

BRAKES

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Parking Brake	Park In-Transmission

ADDITIONAL SPECIFICATIONS

Adjustable Driver Seat	Standard
Cargo System	Lock & Ride®
Color / Graphics	Azure Crystal Metallic
Electronic Power Steering	Standard
Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, 2 DC Outlets, 1 USB Charge Port
Lighting	Dual LED Headlamps 1250lm Low Beam 2300lm High Beam Dual LED Taillamps
Other Standard Features	Premium Cut & Sew Seats with Contoured Seatbacks and Embroidered Polaris Branding, Premium Steering Wheel and Interior Accents, Polaris Pulse Electrical System (6 position), Standard In-Dash SAE Charge Port, NFC Front Badge
RIDE COMMAND+	Available
Tilt Steering	Standard

TIRES / WHEELS

Front Tires	27 x 9-14; Pro Armor X-Terrain
Rear Tires	27 x 11-14; Pro Armor X-Terrain
Tire Ply Rating	8 Ply Rated
Wheels	14 in. (35.6 cm) Aluminum

SUSPENSION

Front Suspension	Dual A-Arm 11 in (27.9 cm) Travel
Rear Suspension	Dual A-Arm, IRS 11 in (27.9 cm) Travel
Turning Radius	17 ft (518 cm)