

# RZR Pro R 4 Troy Lee Designs Edition Electric Blue



## Key Specifications

**225**  
HP

**75.8"**  
WIDTH

**16"**  
CLEARANCE

## ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	1997cc
Drive System Type	Pro Performance True 2WD/4WD/4WD Lock
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke DOHC Inline Four Cylinder
Fuel System/Battery	Electronic Fuel Injection
Horsepower	225 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

## DIMENSIONS

Bed Box Dimensions (L x W x H)	29.5 x 23.8 x 8.1 in (75 x 60.5 x 20.6 cm)
Box Capacity	300 lb (136 kg)
Estimated Dry Weight	2581 lb
Fuel Capacity	12 gal (45.4 L)
Ground Clearance	16 in (40.6 cm)
Hitch Towing Rating	N/A
Overall Vehicle Size (L x W x H)	165.5 x 75.8 x 76.5" (420 x 188 x 194 cm)
Payload Capacity	900 lb (408 kg)
Wheelbase	133.5 in (339.1cm)

## BRAKES

<b>Front/Rear Brakes</b>	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers; Aluminum Top Hat Rotor
<b>Parking Brake</b>	Park In-Transmission

## ADDITIONAL SPECIFICATIONS

<b>Cargo System</b>	Lock & Ride; Convertible Fold Flat rear seat storage with integrated tie downs points, 27.7 x 52.8 x 19.5" (70.4 x 134.1 x 49.53 cm) Factory Equipped Cargo Liner
<b>Doors</b>	Front & Rear Full Doors
<b>Electronic Power Steering</b>	Rack Mounted High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel with Tilt and Telescoping Adjustment; DYNAMIX DV with Integrated EPS Modes and Ride Command Push Button Controls
<b>Hitch Type</b>	Not Equipped
<b>Instrumentation</b>	RIDE COMMAND™ 7" Glove-Touch Display: Built-In GPS, Mapping, Vehicle-to-Vehicle with *Group Ride, Follow the Leader, & Messaging. Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets, Rockford Fosgate® Stage 4 H.O. Audio System featuring a 400W 10" Subwoofer, 4x 100W HO Speakers, Dual-sweep Analog Dials w/ 4 in LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals. Digital Instrumentation: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator
<b>Lighting</b>	Signature White LED, Rigid 32" Combo LED light bar, Low/High & Red LED Tail / Brake Lights; Front, Rear, Speaker Lighting, and Interior Accent Lighting
<b>Other Standard Features</b>	Troy Lee Design Paint & Graphics Package, Limited Edition Numbered Badge, RIDE COMMAND®, Rear Camera, High Output External 1700W Alternator, Polaris Pulse System, In-Dash Charge Port, 2 front DC Accy ports, Polaris P.A.S.S., Driver & Passenger Door Bags, Painted Aluminum Roof, Painted Front & Rear Bumpers, Painted Rock Sliders, Colored Matched Toe Link, Hood Scoop, Mud and Rock Guards, User Selectable Throttle Modes (Sport, Rock, & Race)
<b>RIDE COMMAND+</b>	Factory-Installed
<b>Seat Type</b>	Color-Matched, Front Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat sliders with tilt adjustability) and Retractable Click-6 Harnesses, Rear Stadium style seating with non-retractable 6-point harnesses

## TIRES / WHEELS

<b>Front Tires</b>	33 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7
<b>Rear Tires</b>	33 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7
<b>Wheels</b>	Cast Aluminum Beadlock

# SUSPENSION

<b>Electronic Suspension Control System</b>	Dynamix DV with Selectable Ride Modes: Comfort, Rock, Track, Baja
<b>Front Shocks</b>	FOX 3.0 Live Valve X2 Internal Bypass (Electronically Controlled Compression and Rebound)
<b>Front Suspension</b>	Light Weight Boxed Dual A-Arm with 3 piece Stabilizer Bar and 27.0" (68.6 cm) Usable Travel, 22.25" (56.5 cm) Wheel Travel, Unitized Hubs
<b>Rear Shocks</b>	FOX 3.0 Live Valve X2 Internal Bypass (Electronically Controlled Compression and Rebound)
<b>Rear Suspension</b>	Boxed Trailing Arm with Toe Link, High-Clearance Radius Rods, and 3 piece Stabilizer Bar and 29.0" (73.7cm) Usable Travel, 24.5" (62.2 cm) Wheel Travel, Unitized Hubs