GENERAL XP 1000 Premium Black Crystal



Key Specifications			
100 нр	64" WIDTH	13.5" Ground clearance	
	• •		

ENGINE & DRIVETRAIN

Cooling	Liquid
Drive System Type	On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	EDA: Engine Deceleration Assist
Engine Type	ProStar 1000; 4-Stroke DOHC Twin Cylinder
Fuel System/Battery	Electronic Fuel Injection
Horsepower / Displacement	100 hp / 999 cc
Transmission/Final Drive	Automatic PVT P/R/N/L/H

DIMENSIONS

Bed Box Dimensions (L x W x H)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)
Box Capacity	600 lb (272 kg) Rear Dumping Box
Dry Weight	1,666 lb (755 kg)
Fuel Capacity	9.5 gal (35.9 L)
Ground Clearance	13.5" (34.3 cm)
Hitch Towing Rating	1,500 lb (680 kg)
Hitch Type	Standard/2" (5.08 cm) Receiver
Overall Vehicle Size (L x W x H)	118.2 x 64 x 76.5" (300.2 x 162.5 x 194.3 cm)
Payload Capacity	1,100 lb (499 kg)
Person Capacity	2
Stance	64"
Wheelbase	83" (211 cm)

BRAKES

Front/Rear Brakes

Parking Brake

4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers

Park In-Transmission

ADDITIONAL SPECIFICATIONS

Cargo System	Lock & Ride [®]
Electronic Power Steering	High Output EPS
Ingress / Egress	Half Doors Standard
Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet
Lighting	LED Headlight w/ Accent & LED Taillights
Other Standard Features	POLARIS HD 4500 LB Winch w/ Synthetic Rope, Aluminum Fairlead & Rubber Isolator Sport Low Profile Front Bumper ProFit Sport Roof Rockford Fosgate Stage 1 Audio
Seat Type	Bolstered Bucket Seats with Driver Seat Slider and Height Adjustable Seat Belts
Tilt Steering	Standard

TIRES / WHEELS

Front Tires	30 x 10-15; Pro Armor Crawler XGF or ITP Ultra Cross® R Spec
Rear Tires	30 x 10-15; Pro Armor Crawler XG or ITP Ultra Cross® R Spec
Wheels	15" Aluminum

SUSPENSION

Front Shocks	Walker Evans Velocity Series Shocks
Front Suspension	Long Travel, High Clearance Dual A-Arm with Stabilizer Bar, 14" (35.6 cm) Travel
Rear Shocks	Walker Evans Velocity Series Shocks
Rear Suspension	Long Travel, High Clearance Dual Arm IRS with Stabilizer Bar, 14" (35.6) Travel